



Style Specifications – Contour Series

All floors shown or listed in this specification shall be Centiva Contour Series by International Floors of America, Inc., Florence, AL, 35630.

Specific product shall be: in size " x "
Style Color Series Surface Edge

The Centiva Contour Series shall be constructed with a .032" high density wearlayer. All products shall have an overall gauge of .120" (3 mm) nominal. See individual product specification for sizes offered in each line. The resilient tile shall be manufactured in accordance with ASTM Specification F-1700, and shall be asbestos free. All products shall have a Commercial Limited 20-year Wear Warranty and Residential Lifetime Wear Warranty. The adhesive shall be CENTI 2001 WET SET, CENTI 2000 EP, or CENTI 6000 SP. Installation shall be in accordance with the latest Centiva Installation Guidelines found at www.centiva.com.

The Contour Series square tiles are recommended to be installed using the one-quarter turn installation method for best design appeal and results. Rectangular shaped tiles should be installed in one direction.

CONTOUR SERIES – FESTIVAL

ADAGIO

FE 0785-C Adagio Blue

Classification:	ASTM F 1700 Class III Solid Vinyl Tile		
Construction:	Multiple layers with backing which contains pre- and post-consumer material		
Overall Thickness:	.120" / 3 mm (nominal)		
Wearlayer Thickness:	.032" clear, rigid high density PVC		
Size:	12" x 12", 18" x 18", plus additional custom sizes		
Edge:	Square, Slight Bevel		
Surface Texture:	Frost (FR) <i>recommended</i> , Fresco (FC), Pathway (PH), Quarry (QU)		
Standard Colors:	1 color		
Warranty:	20 years Commercial, Lifetime Residential		
Recycling:	Suitable		
Test Performance:	ASTM E 648	Critical Radiant Flux	Class I CRF>0.45
	ASTM E 662	Smoke Density	<450; Good
	ASTM F 925	Chemical Resistance	Excellent
	Slip Resistance	ASTM C 1028*	Very Good (*textures)
		ASTM D 2047	Passes
		ADA Compliant	FTC Slip Resistant Classified Product

ASPHALT

FE 0721-C Asphalt FE 0722-C Arizona Asphalt

Classification:	ASTM F 1700 Class III Solid Vinyl Tile		
Construction:	Multiple layers with backing which contains pre- and post-consumer material		
Overall Thickness:	.120" / 3 mm (nominal)		
Wearlayer Thickness:	.032" clear, rigid high density PVC		
Size:	18" x 18" (only)		
Edge:	Square, Slight Bevel		
Surface Texture:	Pathway (PH) <i>recommended</i> , Fresco (FC), Frost (FR), Quarry (QU)		
Standard Colors:	2 colors		
Warranty:	20 years Commercial, Lifetime Residential		
Recycling:	Suitable		
Test Performance:	ASTM E 648	Critical Radiant Flux	Class I CRF>0.45
	ASTM E 662	Smoke Density	<450; Good
	ASTM F 925	Chemical Resistance	Excellent
	Slip Resistance	ASTM C 1028*	Very Good(*textures)
		ASTM D 2047	Passes
		ADA Compliant	FTC Slip Resistant Classified Product

BETON

FE 7220-C Dune FE 7221-C Thunder FE 7222-C Cloud
FE 7223-C Meadow FE 7224-C Clay FE 7225-C Terracota

Classification:	ASTM F 1700 Class III Solid Vinyl Tile		
Construction:	Multiple layers with backing which contains pre- and post-consumer material		
Overall Thickness:	.120" / 3 mm (nominal)		
Wearlayer Thickness:	.032" clear, rigid high density PVC		
Size:	12" x 12", 12" x 18", 18" x 18", 12" x 36", 18" x 36", 36" x 36", 4" x 36", 6" x 36" plus additional custom sizes		
Edge:	Square, Slight Bevel		
Surface Texture:	Pathway (PH) <i>recommended</i> , Fresco (FC), Frost (FR), Quarry (QU)		
Standard Colors:	6 colors		
Warranty:	20 years Commercial, Lifetime Residential		
Recycling:	Suitable		
Test Performance:	ASTM E 648	Critical Radiant Flux	Class I CRF>0.45
	ASTM E 662	Smoke Density	<450; Good
	ASTM F 925	Chemical Resistance	Excellent
	Slip Resistance	ASTM C 1028*	Very Good(*textures)
		ASTM D 2047	Passes
		ADA Compliant	FTC Slip Resistant Classified Product

CONCRETE II

FE 7303-C Concrete II Gray FE 7305-C Concrete II Brick FE 7307-C Concrete II Tan

Classification:	ASTM F 1700 Class III Solid Vinyl Tile		
Construction:	Multiple layers with backing which contains pre- and post-consumer material		
Overall Thickness:	.120" / 3 mm (nominal)		
Wearlayer Thickness:	.032" clear, rigid high density PVC		
Size:	18" x 18", 12" x 36", 18" x 36", 36" x 36", plus additional custom sizes		
Edge:	Square, Slight Bevel		
Surface Texture:	Quarry (QU) <i>recommended</i> , Fresco (FC), Frost (FR), Pathway (PH)		
Standard Colors:	3 colors		
Warranty:	20 years Commercial, Lifetime Residential		
Recycling:	Suitable		
Test Performance:	ASTM E 648	Critical Radiant Flux	Class I CRF>0.45
	ASTM E 662	Smoke Density	<450; Good
	ASTM F 925	Chemical Resistance	Excellent
	Slip Resistance	ASTM C 1028*	Very Good(*textures)
		ASTM D 2047	Passes
		ADA Compliant	FTC Slip Resistant Classified Product

SIGMA

FE 0745-C Pure FE 0747-C Phantom FE 0749-C Nature

Classification:	ASTM F 1700 Class III Solid Vinyl Tile		
Construction:	Multiple layers with backing which contains pre- and post-consumer material		
Overall Thickness:	.120" / 3 mm (nominal)		
Wearlayer Thickness:	.032" clear, rigid high density PVC		
Size:	12" x 12", 18" x 18", 4" x 36", 6" x 36" plus additional custom sizes		
Edge:	Square, Slight Bevel		
Surface Texture:	Frost (FR) <i>recommended</i> , Fresco (FC), Pathway (PH), Quarry (QU)		
Standard Colors:	3 colors		
Warranty:	20 years Commercial, Lifetime Residential		
Recycling:	Suitable		
Test Performance:	ASTM E 648	Critical Radiant Flux	Class I CRF>0.45
	ASTM E 662	Smoke Density	<450; Good
	ASTM F 925	Chemical Resistance	Excellent
	Slip Resistance	ASTM C 1028*	Very Good (*textures)
		ASTM D 2047	Passes
		ADA Compliant	FTC Slip Resistant Classified Product

TIDE

FE 0701-C Night Tide FE 0705-C Dusk Tide FE 0707-C Evening Tide

Classification:	ASTM F 1700 Class III Solid Vinyl Tile		
Construction:	Multiple layers with backing which contains pre- and post-consumer material		
Overall Thickness:	.120" / 3 mm (nominal)		
Wearlayer Thickness:	.032" clear, rigid high density PVC		
Size:	12" x 12", 12" x 18", 18" x 18", 12" x 36", 18" x 36", 36" x 36", 4" x 36", 6" x 36" plus additional custom sizes		
Edge:	Square, Slight Bevel		
Surface Texture:	Frost (FR) <i>recommended</i> , Fresco (FC), Pathway (PH), Quarry (QU)		
Standard Colors:	3 colors		
Warranty:	20 years Commercial, Lifetime Residential		
Recycling:	Suitable		
Test Performance:	ASTM E 648	Critical Radiant Flux	Class I CRF>0.45
	ASTM E 662	Smoke Density	<450; Good
	ASTM F 925	Chemical Resistance	Excellent
	Slip Resistance	ASTM C 1028*	Very Good (*textures)
		ASTM D 2047	Passes
		ADA Compliant	FTC Slip Resistant Classified Product

WEAVE

FE 0711-C Greenweave

Classification:	ASTM F 1700 Class III Solid Vinyl Tile		
Construction:	Multiple layers with backing which contains pre- and post-consumer material		
Overall Thickness:	.120" / 3 mm (nominal)		
Wearlayer Thickness:	.032" clear, rigid high density PVC		
Size:	18" x 18" (only)		
Edge:	Square, Slight Bevel		
Surface Texture:	Frost (FR) <i>recommended</i> , Fresco (FC), Pathway (PH), Quarry (QU)		
Standard Colors:	1 color		
Warranty:	20 years Commercial, Lifetime Residential		
Recycling:	Suitable		
Test Performance:	ASTM E 648	Critical Radiant Flux	Class I CRF>0.45
	ASTM E 662	Smoke Density	<450; Good
	ASTM F 925	Chemical Resistance	Excellent
	Slip Resistance	ASTM C 1028*	Very Good (*textures)
		ASTM D 2047	Passes
		ADA Compliant	FTC Slip Resistant Classified Product



CONTOUR SERIES – STONE

AEGEAN

CS 0501-C Aegean Sea

Classification:	ASTM F 1700 Class III Solid Vinyl Tile		
Construction:	Multiple layers with backing which contains pre- and post-consumer material		
Overall Thickness:	.120" / 3 mm (nominal)		
Wearlayer Thickness:	.032" clear, rigid high density PVC		
Size:	12" x 12" (only)		
Edge:	Square, Slight Bevel		
Surface Texture:	Quarry (QU) <i>recommended</i> , Fresco (FC), Frost (FR), Pathway (PH)		
Standard Colors:	1 color		
Warranty:	20 years Commercial, Lifetime Residential		
Recycling:	Suitable		
Test Performance:	ASTM E 648	Critical Radiant Flux	Class I CRF>0.45
	ASTM E 662	Smoke Density	<450; Good
	ASTM F 925	Chemical Resistance	Excellent
	Slip Resistance	ASTM C 1028*	Very Good (*textures)
		ASTM D 2047	Passes
		ADA Compliant	FTC Slip Resistant Classified Product

ANCIENT STONE

CS 0531-C Parthenon Gold CS 0562-C Alcantara

Classification:	ASTM F 1700 Class III Solid Vinyl Tile		
Construction:	Multiple layers with backing which contains pre- and post-consumer material		
Overall Thickness:	.120" / 3 mm (nominal)		
Wearlayer Thickness:	.032" clear, rigid high density PVC		
Size:	12" x 12", 18" x 18", plus additional custom sizes		
Edge:	Square, Slight Bevel		
Surface Texture:	Pathway (PH) <i>recommended</i> , Fresco (FC), Frost (FR), Quarry (QU)		
Standard Colors:	2 colors		
Warranty:	20 years Commercial, Lifetime Residential		
Recycling:	Suitable		
Test Performance:	ASTM E 648	Critical Radiant Flux	Class I CRF>0.45
	ASTM E 662	Smoke Density	<450; Good
	ASTM F 925	Chemical Resistance	Excellent
	Slip Resistance	ASTM C 1028*	Very Good (*textures)
		ASTM D 2047	Passes
		ADA Compliant	FTC Slip Resistant Classified Product

ARCADIAN

CS 0541-C Arcadian Pilar CS 0542-C Arcadian Column CS 0544-C Arcadian Arch

Classification:	ASTM F 1700 Class III Solid Vinyl Tile		
Construction:	Multiple layers with backing which contains pre- and post-consumer material		
Overall Thickness:	.120" / 3 mm (nominal)		
Wearlayer Thickness:	.032" clear, rigid high density PVC		
Size:	12" x 12", 18" x 18", plus additional custom sizes		
Edge:	Square, Slight Bevel		
Surface Texture:	Quarry (QU) <i>recommended</i> , Fresco (FC), Frost (FR), Pathway (PH)		
Standard Colors:	3 colors		
Warranty:	20 years Commercial, Lifetime Residential		
Recycling:	Suitable		
Test Performance:	ASTM E 648	Critical Radiant Flux	Class I CRF>0.45
	ASTM E 662	Smoke Density	<450; Good
	ASTM F 925	Chemical Resistance	Excellent
	Slip Resistance	ASTM C 1028*	Very Good (*textures)
		ASTM D 2047	Passes
		ADA Compliant	FTC Slip Resistant Classified Product

ATLANTIS

CS 0521-C Atlantis Bone CS 0522-C Atlantis Beige CS 0523-C Atlantis Metal
CS 7241-C Atlantis Brown CS 7242-C Atlantis Blue CS 7243-C Atlantis Gray

Classification: ASTM F 1700 Class III Solid Vinyl Tile
Construction: Multiple layers with backing which contains pre- and post-consumer material
Overall Thickness: .120" / 3 mm (nominal)
Wearlayer Thickness: .032" clear, rigid high density PVC
Size: 12" x 12", 12" x 18", 18" x 18", 12" x 36", 18" x 36", 36" x 36" plus additional custom sizes
Edge: Square, Slight Bevel
Surface Texture: Quarry (QU) *recommended*, Fresco (FC), Frost (FR), Pathway (PH)
Standard Colors: 6 colors
Warranty: 20 years Commercial, Lifetime Residential
Recycling: Suitable
Test Performance:

ASTM E 648	Critical Radiant Flux	Class I CRF>0.45
ASTM E 662	Smoke Density	<450; Good
ASTM F 925	Chemical Resistance	Excellent
Slip Resistance	ASTM C 1028*	Very Good (*textures)
	ASTM D 2047	Passes
	ADA Compliant	FTC Slip Resistant Classified Product

CLASSICO

CS 0511-C Classico Grey CS 0513-C Classico Carmel CS 0515-C Classico Verde

Classification: ASTM F 1700 Class III Solid Vinyl Tile
Construction: Multiple layers with backing which contains pre- and post-consumer material
Overall Thickness: .120" / 3 mm (nominal)
Wearlayer Thickness: .032" clear, rigid high density PVC
Size: 12" x 12", 18" x 18", plus additional custom sizes
Edge: Square, Slight Bevel
Surface Texture: Frost (FR) *recommended*, Fresco (FC), Pathway (PH), Quarry (QU)
Standard Colors: 3 colors
Warranty: 20 years Commercial, Lifetime Residential
Recycling: Suitable
Test Performance:

ASTM E 648	Critical Radiant Flux	Class I CRF>0.45
ASTM E 662	Smoke Density	<450; Good
ASTM F 925	Chemical Resistance	Excellent
Slip Resistance	ASTM C 1028*	Very Good (*textures)
	ASTM D 2047	Passes
	ADA Compliant	FTC Slip Resistant Classified Product

MODERN LIME

CS 0602-C Lagos CS 0604-C Porto CS 0606-C Mocha CS 0608-C Branco CS 0610-C Valleta
CS 0612-C Camino CS 0614-C Calypso CS 0616-C Costa CS 0618-C Volga CS 0620-C Niko

Classification: ASTM F 1700 Class III Solid Vinyl Tile
Construction: Multiple layers with backing which contains pre- and post-consumer material
Overall Thickness: .120" / 3 mm (nominal)
Wearlayer Thickness: .032" clear, rigid high density PVC
Size: 12" x 12", 18" x 18", 36" x 36", plus additional custom sizes
Edge: Square, Slight Bevel
Surface Texture: Quarry (QU) *recommended*, Fresco (FC), Frost (FR), Pathway (PH)
Standard Colors: 10 colors
Warranty: 20 years Commercial, Lifetime Residential
Recycling: Suitable
Test Performance:

ASTM E 648	Critical Radiant Flux	Class I CRF>0.45
ASTM E 662	Smoke Density	<450; Good
ASTM F 925	Chemical Resistance	Excellent
Slip Resistance	ASTM C 1028*	Very Good (*textures)
	ASTM D 2047	Passes
	ADA Compliant	FTC Slip Resistant Classified Product

Style Specifications – Contour Series



PORTOKALI

CS 0561-C Portokali

Classification:	ASTM F 1700 Class III Solid Vinyl Tile		
Construction:	Multiple layers with backing which contains pre- and post-consumer material		
Overall Thickness:	.120" / 3 mm (nominal)		
Wearlayer Thickness:	.032" clear, rigid high density PVC		
Size:	12" x 12", 18" x 18", plus additional sizes		
Edge:	Square, Slight Bevel		
Surface Texture:	Fresco (FC) <i>recommended</i> , Quarry (QU), Frost (FR), Pathway (PH)		
Standard Colors:	1 color		
Warranty:	20 years Commercial, Lifetime Residential		
Recycling:	Suitable		
Test Performance:	ASTM E 648	Critical Radiant Flux	Class I CRF>0.45
	ASTM E 662	Smoke Density	<450; Good
	ASTM F 925	Chemical Resistance	Excellent
	Slip Resistance	ASTM C 1028*	Very Good(*textures)
		ASTM D 2047	Passes
		ADA Compliant	FTC Slip Resistant Classified Product

SANTORINI

CS 0551-C Santorini Kafe CS 0553-C Santorini Tandem CS 0557-C Santorini Argos

Classification:	ASTM F 1700 Class III Solid Vinyl Tile		
Construction:	Multiple layers with backing which contains pre- and post-consumer material		
Overall Thickness:	.120" / 3 mm (nominal)		
Wearlayer Thickness:	.032" clear, rigid high density PVC		
Size:	12" x 12", 18" x 18", plus additional custom sizes		
Edge:	Square, Slight Bevel		
Surface Texture:	Pathway (PH) <i>recommended</i> , Fresco (FC), Frost (FR), Quarry (QU)		
Standard Colors:	3 colors		
Warranty:	20 years Commercial, Lifetime Residential		
Recycling:	Suitable		
Test Performance:	ASTM E 648	Critical Radiant Flux	Class I CRF>0.45
	ASTM E 662	Smoke Density	<450; Good
	ASTM F 925	Chemical Resistance	Excellent
	Slip Resistance	ASTM C 1028*	Very Good(*textures)
		ASTM D 2047	Passes
		ADA Compliant	FTC Slip Resistant Classified Product

CONTOUR SERIES – WOOD

BLOCKWOOD CP 1201-C Caramel Blockwood CP 1202-C Auburn Blockwood

Classification:	ASTM F 1700 Class III Solid Vinyl Tile		
Construction:	Multiple layers with backing which contains pre- and post-consumer material		
Overall Thickness:	.120" / 3 mm (nominal)		
Wearlayer Thickness:	.032" clear, rigid high density PVC		
Size:	36" x 36" (only)		
Edge:	Square, Slight Bevel		
Surface Texture:	Quarry (QU) <i>recommended</i> , Frost (FR)		
Standard Colors:	2 colors		
Warranty:	20 years Commercial, Lifetime Residential		
Recycling:	Suitable		
Test Performance:	ASTM E 648	Critical Radiant Flux	Class I CRF>0.45
	ASTM E 662	Smoke Density	<450; Good
	ASTM F 925	Chemical Resistance	Excellent
	Slip Resistance	ASTM C 1028*	Very Good (*textures)
		ASTM D 2047	Passes
		ADA Compliant	FTC Slip Resistant Classified Product

CONTOUR PLANK

CP 3104-C Atlantic Cherry	CP 3105-C Aged Cherry	CP 3106-C Bergerac Beech
CP 3201-C Grappa Noce	CP 3205-C Kingwood	CP 3207-C Bolivian Rosewood
CP 3210-C Brazilian Cherry	CP 3213-C Trio Walnut	CP 3214-C Camphor Wood
CP 3206-C Merrill Birch	CP 3306-C Canadian Maple	CP 3310-C Queensland Walnut
CP 3311-C Hawaiian Teak	CP 3312-C Golden Teak	CP 3324-C Washed Teak
CP 3313-C Golden Rosewood	CP 0305-C Vintage Tower	CP 0303-C Vintage Chalet
CP 0301-C Vintage Lodge	CP 0302-C Vintage Cabin	CP 0306-C Vintage Inn
CP 0311-C Summer Savannah	CP 0321-C High Forest	CP 0333-C English Flat
CP 3302-C Fruitwood	CP 3301-C Zebrano	CP 3314-C Brown Strata
CP 3316-C Olive Strata	CP 3322-C Pale Strata	CP 0355-C Pacific Lighthouse
CP 0357-C Driftwood	CP 0359-C Rustic Cedar	CP 0351-C Pacific Boathouse
CP 0353-C Pacific Shorehouse	CP 3510-C Metallic Green	CP 3511-C Metallic Gray
CP 3512-C Metallic Black	CP 0361-C Newborn	CP 0383-C Wild Bohemian
CP 0381-C Wild BosaNova	CP 3320-C Strand Bamboo	

Classification:	ASTM F 1700 Class III Solid Vinyl Tile		
Construction:	Multiple layers with backing which contains pre- and post-consumer material		
Overall Thickness:	.120" / 3 mm (nominal)		
Wearlayer Thickness:	.032" clear, rigid high density PVC		
Size:	4" x 36", 6" x 36", or 7.2" x 48"		
Edge:	Square, Slight Bevel		
Surface Texture:	Frost (FR), Natural Grain (NG), Rough (RG), Sawn (SW), Tick (TK) Recommended surface for each product is shown on sample in sample book		
Standard Colors:	44		
Warranty:	20 years Commercial, Lifetime Residential		
Recycling:	Suitable		
Test Performance:	ASTM E 648	Critical Radiant Flux	Class I CRF>0.45
	ASTM E 662	Smoke Density	<450; Good
	ASTM F 925	Chemical Resistance	Excellent
	Slip Resistance	ASTM C 1028*	Very Good (*textures)
		ASTM D 2047	Passes
		ADA Compliant	FTC Slip Resistant Classified Product