



Style Specifications – Contour Series

All floors shown or listed in this specification shall be Centiva Contour Series by International Floors of America, Inc., Florence, AL, 35630.

Specific product shall be: __ __ __ __ __ __ __ __ __ __ __ __ in size __" x __"
Style Color Series Surface Edge

The Centiva Contour Series shall be constructed with a .032" high density wearlayer. All products shall have an overall gauge of .120" (3 mm) nominal. See individual product specification for sizes offered in each line. The resilient tile shall be manufactured in accordance with ASTM Specification F-1700, and shall be asbestos free. All products shall have a Commercial Limited 20-year Wear Warranty and Residential Lifetime Wear Warranty. The adhesive shall be CENTI 2001 WET SET, CENTI 2000 EP, or CENTI 6000 SP. Installation shall be in accordance with the latest Centiva Installation Guidelines found at www.centiva.com.

The Contour Series square tiles are recommended to be installed using the one-quarter turn installation method for best design appeal and results. Rectangular shaped tiles should be installed in one direction.

CONTOUR SERIES – FESTIVAL

ADAGIO

FE 0785-C Adagio Blue

| | | | |
|-----------------------------|---|---------------------------------------|-----------------------|
| Classification: | ASTM F 1700 Class III Solid Vinyl Tile | | |
| Construction: | Multiple layers with backing which contains pre- and post-consumer material | | |
| Overall Thickness: | .120" / 3 mm (nominal) | | |
| Wearlayer Thickness: | .032" clear, rigid high density PVC | | |
| Size: | 12" x 12", 18" x 18", plus additional custom sizes | | |
| Edge: | Square, Slight Bevel | | |
| Surface Texture: | Frost (FR) <i>recommended</i> , Fresco (FC), Pathway (PH), Quarry (QU) | | |
| Standard Colors: | 1 color | | |
| Warranty: | 20 years Commercial, Lifetime Residential | | |
| Recycling: | Suitable | | |
| Test Performance: | ASTM E 648 | Critical Radiant Flux | Class I CRF > 0.45 |
| | ASTM E 662 | Smoke Density | < 450; Good |
| | ASTM F 925 | Chemical Resistance | Excellent |
| | Slip Resistance | ASTM C 1028* | Very Good (*textures) |
| | | ASTM D 2047 | Passes |
| | ADA Compliant | FTC Slip Resistant Classified Product | |

ASPHALT

FE 0721-C Asphalt FE 0722-C Arizona Asphalt

| | | | |
|-----------------------------|---|-----------------------|---------------------------------------|
| Classification: | ASTM F 1700 Class III Solid Vinyl Tile | | |
| Construction: | Multiple layers with backing which contains pre- and post-consumer material | | |
| Overall Thickness: | .120" / 3 mm (nominal) | | |
| Wearlayer Thickness: | .032" clear, rigid high density PVC | | |
| Size: | 18" x 18" (only) | | |
| Edge: | Square, Slight Bevel | | |
| Surface Texture: | Pathway (PH) <i>recommended</i> , Fresco (FC), Frost (FR), Quarry (QU) | | |
| Standard Colors: | 2 colors | | |
| Warranty: | 20 years Commercial, Lifetime Residential | | |
| Recycling: | Suitable | | |
| Test Performance: | ASTM E 648 | Critical Radiant Flux | Class I CRF>0.45 |
| | ASTM E 662 | Smoke Density | <450; Good |
| | ASTM F 925 | Chemical Resistance | Excellent |
| | Slip Resistance | ASTM C 1028* | Very Good(*textures) |
| | | ASTM D 2047 | Passes |
| | | ADA Compliant | FTC Slip Resistant Classified Product |

BETON

FE 7220-C Dune FE 7221-C Thunder FE 7222-C Cloud
FE 7223-C Meadow FE 7224-C Clay FE 7225-C Terracota

| | | | |
|-----------------------------|--|-----------------------|---------------------------------------|
| Classification: | ASTM F 1700 Class III Solid Vinyl Tile | | |
| Construction: | Multiple layers with backing which contains pre- and post-consumer material | | |
| Overall Thickness: | .120" / 3 mm (nominal) | | |
| Wearlayer Thickness: | .032" clear, rigid high density PVC | | |
| Size: | 12" x 12", 12" x 18", 18" x 18", 12" x 36", 18" x 36", 36" x 36", 4" x 36", 6" x 36" plus additional custom sizes | | |
| Edge: | Square, Slight Bevel | | |
| Surface Texture: | Pathway (PH) <i>recommended</i> , Fresco (FC), Frost (FR), Quarry (QU) | | |
| Standard Colors: | 6 colors | | |
| Warranty: | 20 years Commercial, Lifetime Residential | | |
| Recycling: | Suitable | | |
| Test Performance: | ASTM E 648 | Critical Radiant Flux | Class I CRF>0.45 |
| | ASTM E 662 | Smoke Density | <450; Good |
| | ASTM F 925 | Chemical Resistance | Excellent |
| | Slip Resistance | ASTM C 1028* | Very Good(*textures) |
| | | ASTM D 2047 | Passes |
| | | ADA Compliant | FTC Slip Resistant Classified Product |

CONCRETE II

FE 7303-C Concrete II Gray FE 7305-C Concrete II Brick FE 7307-C Concrete II Tan

| | | | |
|-----------------------------|---|-----------------------|---------------------------------------|
| Classification: | ASTM F 1700 Class III Solid Vinyl Tile | | |
| Construction: | Multiple layers with backing which contains pre- and post-consumer material | | |
| Overall Thickness: | .120" / 3 mm (nominal) | | |
| Wearlayer Thickness: | .032" clear, rigid high density PVC | | |
| Size: | 18" x 18", 12" x 36", 18" x 36", 36" x 36", plus additional custom sizes | | |
| Edge: | Square, Slight Bevel | | |
| Surface Texture: | Quarry (QU) <i>recommended</i> , Fresco (FC), Frost (FR), Pathway (PH) | | |
| Standard Colors: | 3 colors | | |
| Warranty: | 20 years Commercial, Lifetime Residential | | |
| Recycling: | Suitable | | |
| Test Performance: | ASTM E 648 | Critical Radiant Flux | Class I CRF>0.45 |
| | ASTM E 662 | Smoke Density | <450; Good |
| | ASTM F 925 | Chemical Resistance | Excellent |
| | Slip Resistance | ASTM C 1028* | Very Good(*textures) |
| | | ASTM D 2047 | Passes |
| | | ADA Compliant | FTC Slip Resistant Classified Product |

Style Specifications – Contour Series



CUBIST

FE 0751-C Armour FE 0752-C Nickel FE 0754-C Crescent
FE 0755-C Brass FE 0756-C Tortoise Shell

Classification: ASTM F 1700 Class III Solid Vinyl Tile
Construction: Multiple layers with backing which contains pre- and post-consumer material
Overall Thickness: .120" / 3 mm (nominal)
Wearlayer Thickness: .032" clear, rigid high density PVC
Size: 12" x 12", 18" x 18", 12" x 36", plus additional custom sizes
Edge: Square, Slight Bevel
Surface Texture: Frost (FR) *recommended*, Fresco (FC), Pathway (PH), Quarry (QU)
Standard Colors: 5 colors
Warranty: 20 years Commercial, Lifetime Residential
Recycling: Suitable
Test Performance: ASTM E 648 Critical Radiant Flux Class I CRF>0.45
ASTM E 662 Smoke Density <450; Good
ASTM F 925 Chemical Resistance Excellent
Slip Resistance ASTM C 1028* Very Good("textures)
 ASTM D 2047 Passes
 ADA Compliant FTC Slip Resistant Classified Product

RAYS

FE 0791-C Peridot FE 0792-C Sunglow FE 0793-C Graphite FE 0794-C Amber
FE 0795-C Ore FE 0796-C Azure FE 0797-C Platinum

Classification: ASTM F 1700 Class III Solid Vinyl Tile
Construction: Multiple layers with backing which contains pre- and post-consumer material
Overall Thickness: .120" / 3 mm (nominal)
Wearlayer Thickness: .032" clear, rigid high density PVC
Size: 12" x 12", 12" x 18", 18" x 18", 12" x 36", 18" x 36", 36" x 36", 4" x 36", 6" x 36"
plus additional custom sizes
Edge: Square, Slight Bevel
Surface Texture: Frost (FR) *recommended*, Fresco (FC), Pathway (PH), Quarry (QU)
Standard Colors: 7 colors
Warranty: 20 years Commercial, Lifetime Residential
Recycling: Suitable
Test Performance: ASTM E 648 Critical Radiant Flux Class I CRF>0.45
ASTM E 662 Smoke Density <450; Good
ASTM F 925 Chemical Resistance Excellent
Slip Resistance ASTM C 1028* Very Good("textures)
 ASTM D 2047 Passes
 ADA Compliant FTC Slip Resistant Classified Product

SIGMA

FE 0745-C Pure FE 0747-C Phantom FE 0749-C Nature

| | | | |
|-----------------------------|---|-----------------------|---------------------------------------|
| Classification: | ASTM F 1700 Class III Solid Vinyl Tile | | |
| Construction: | Multiple layers with backing which contains pre- and post-consumer material | | |
| Overall Thickness: | .120" / 3 mm (nominal) | | |
| Wearlayer Thickness: | .032" clear, rigid high density PVC | | |
| Size: | 12" x 12", 18" x 18", 4" x 36", 6" x 36" plus additional custom sizes | | |
| Edge: | Square, Slight Bevel | | |
| Surface Texture: | Frost (FR) <i>recommended</i> , Fresco (FC), Pathway (PH), Quarry (QU) | | |
| Standard Colors: | 3 colors | | |
| Warranty: | 20 years Commercial, Lifetime Residential | | |
| Recycling: | Suitable | | |
| Test Performance: | ASTM E 648 | Critical Radiant Flux | Class I CRF>0.45 |
| | ASTM E 662 | Smoke Density | <450; Good |
| | ASTM F 925 | Chemical Resistance | Excellent |
| | Slip Resistance | ASTM C 1028* | Very Good (*textures) |
| | | ASTM D 2047 | Passes |
| | | ADA Compliant | FTC Slip Resistant Classified Product |

TIDE

FE 0701-C Night Tide FE 0705-C Dusk Tide FE 0707-C Evening Tide

| | | | |
|-----------------------------|---|-----------------------|---------------------------------------|
| Classification: | ASTM F 1700 Class III Solid Vinyl Tile | | |
| Construction: | Multiple layers with backing which contains pre- and post-consumer material | | |
| Overall Thickness: | .120" / 3 mm (nominal) | | |
| Wearlayer Thickness: | .032" clear, rigid high density PVC | | |
| Size: | 12" x 12", 12" x 18", 18" x 18", 12" x 36", 18" x 36", 36" x 36", 4" x 36", 6" x 36" plus additional custom sizes | | |
| Edge: | Square, Slight Bevel | | |
| Surface Texture: | Frost (FR) <i>recommended</i> , Fresco (FC), Pathway (PH), Quarry (QU) | | |
| Standard Colors: | 3 colors | | |
| Warranty: | 20 years Commercial, Lifetime Residential | | |
| Recycling: | Suitable | | |
| Test Performance: | ASTM E 648 | Critical Radiant Flux | Class I CRF>0.45 |
| | ASTM E 662 | Smoke Density | <450; Good |
| | ASTM F 925 | Chemical Resistance | Excellent |
| | Slip Resistance | ASTM C 1028* | Very Good (*textures) |
| | | ASTM D 2047 | Passes |
| | | ADA Compliant | FTC Slip Resistant Classified Product |

WEAVE

FE 0711-C Greenweave

| | | | |
|-----------------------------|---|-----------------------|---------------------------------------|
| Classification: | ASTM F 1700 Class III Solid Vinyl Tile | | |
| Construction: | Multiple layers with backing which contains pre- and post-consumer material | | |
| Overall Thickness: | .120" / 3 mm (nominal) | | |
| Wearlayer Thickness: | .032" clear, rigid high density PVC | | |
| Size: | 18" x 18" (only) | | |
| Edge: | Square, Slight Bevel | | |
| Surface Texture: | Frost (FR) <i>recommended</i> , Fresco (FC), Pathway (PH), Quarry (QU) | | |
| Standard Colors: | 1 color | | |
| Warranty: | 20 years Commercial, Lifetime Residential | | |
| Recycling: | Suitable | | |
| Test Performance: | ASTM E 648 | Critical Radiant Flux | Class I CRF>0.45 |
| | ASTM E 662 | Smoke Density | <450; Good |
| | ASTM F 925 | Chemical Resistance | Excellent |
| | Slip Resistance | ASTM C 1028* | Very Good (*textures) |
| | | ASTM D 2047 | Passes |
| | | ADA Compliant | FTC Slip Resistant Classified Product |



CONTOUR SERIES – STONE

AEGEAN

CS 0501-C Aegean Sea

| | | | |
|-----------------------------|---|-----------------------|---------------------------------------|
| Classification: | ASTM F 1700 Class III Solid Vinyl Tile | | |
| Construction: | Multiple layers with backing which contains pre- and post-consumer material | | |
| Overall Thickness: | .120" / 3 mm (nominal) | | |
| Wearlayer Thickness: | .032" clear, rigid high density PVC | | |
| Size: | 12" x 12" (only) | | |
| Edge: | Square, Slight Bevel | | |
| Surface Texture: | Quarry (QU) <i>recommended</i> , Fresco (FC), Frost (FR), Pathway (PH) | | |
| Standard Colors: | 1 color | | |
| Warranty: | 20 years Commercial, Lifetime Residential | | |
| Recycling: | Suitable | | |
| Test Performance: | ASTM E 648 | Critical Radiant Flux | Class I CRF>0.45 |
| | ASTM E 662 | Smoke Density | <450; Good |
| | ASTM F 925 | Chemical Resistance | Excellent |
| | Slip Resistance | ASTM C 1028* | Very Good (*textures) |
| | | ASTM D 2047 | Passes |
| | | ADA Compliant | FTC Slip Resistant Classified Product |

ANCIENT STONE

CS 0531-C Parthenon Gold CS 0562-C Alcantara

| | | | |
|-----------------------------|---|-----------------------|---------------------------------------|
| Classification: | ASTM F 1700 Class III Solid Vinyl Tile | | |
| Construction: | Multiple layers with backing which contains pre- and post-consumer material | | |
| Overall Thickness: | .120" / 3 mm (nominal) | | |
| Wearlayer Thickness: | .032" clear, rigid high density PVC | | |
| Size: | 12" x 12", 18" x 18", plus additional custom sizes | | |
| Edge: | Square, Slight Bevel | | |
| Surface Texture: | Pathway (PH) <i>recommended</i> , Fresco (FC), Frost (FR), Quarry (QU) | | |
| Standard Colors: | 2 colors | | |
| Warranty: | 20 years Commercial, Lifetime Residential | | |
| Recycling: | Suitable | | |
| Test Performance: | ASTM E 648 | Critical Radiant Flux | Class I CRF>0.45 |
| | ASTM E 662 | Smoke Density | <450; Good |
| | ASTM F 925 | Chemical Resistance | Excellent |
| | Slip Resistance | ASTM C 1028* | Very Good (*textures) |
| | | ASTM D 2047 | Passes |
| | | ADA Compliant | FTC Slip Resistant Classified Product |

ARCADIAN

CS 0541-C Arcadian Pilar CS 0542-C Arcadian Column CS 0544-C Arcadian Arch

| | | | |
|-----------------------------|---|-----------------------|---------------------------------------|
| Classification: | ASTM F 1700 Class III Solid Vinyl Tile | | |
| Construction: | Multiple layers with backing which contains pre- and post-consumer material | | |
| Overall Thickness: | .120" / 3 mm (nominal) | | |
| Wearlayer Thickness: | .032" clear, rigid high density PVC | | |
| Size: | 12" x 12", 18" x 18", plus additional custom sizes | | |
| Edge: | Square, Slight Bevel | | |
| Surface Texture: | Quarry (QU) <i>recommended</i> , Fresco (FC), Frost (FR), Pathway (PH) | | |
| Standard Colors: | 3 colors | | |
| Warranty: | 20 years Commercial, Lifetime Residential | | |
| Recycling: | Suitable | | |
| Test Performance: | ASTM E 648 | Critical Radiant Flux | Class I CRF>0.45 |
| | ASTM E 662 | Smoke Density | <450; Good |
| | ASTM F 925 | Chemical Resistance | Excellent |
| | Slip Resistance | ASTM C 1028* | Very Good (*textures) |
| | | ASTM D 2047 | Passes |
| | | ADA Compliant | FTC Slip Resistant Classified Product |

ATLANTIS

CS 0521-C Atlantis Bone CS 0522-C Atlantis Beige CS 0523-C Atlantis Metal
CS 7241-C Atlantis Brown CS 7242-C Atlantis Blue CS 7243-C Atlantis Gray

Classification: ASTM F 1700 Class III Solid Vinyl Tile
Construction: Multiple layers with backing which contains pre- and post-consumer material
Overall Thickness: .120" / 3 mm (nominal)
Wearlayer Thickness: .032" clear, rigid high density PVC
Size: 12" x 12", 12" x 18", 18" x 18", 12" x 36", 18" x 36", 36" x 36" plus additional custom sizes
Edge: Square, Slight Bevel
Surface Texture: Quarry (QU) *recommended*, Fresco (FC), Frost (FR), Pathway (PH)
Standard Colors: 6 colors
Warranty: 20 years Commercial, Lifetime Residential
Recycling: Suitable
Test Performance:

| | | |
|-----------------|-----------------------|---------------------------------------|
| ASTM E 648 | Critical Radiant Flux | Class I CRF>0.45 |
| ASTM E 662 | Smoke Density | <450; Good |
| ASTM F 925 | Chemical Resistance | Excellent |
| Slip Resistance | ASTM C 1028* | Very Good (*textures) |
| | ASTM D 2047 | Passes |
| | ADA Compliant | FTC Slip Resistant Classified Product |

CLASSICO

CS 0511-C Classico Grey CS 0513-C Classico Carmel CS 0515-C Classico Verde

Classification: ASTM F 1700 Class III Solid Vinyl Tile
Construction: Multiple layers with backing which contains pre- and post-consumer material
Overall Thickness: .120" / 3 mm (nominal)
Wearlayer Thickness: .032" clear, rigid high density PVC
Size: 12" x 12", 18" x 18", plus additional custom sizes
Edge: Square, Slight Bevel
Surface Texture: Frost (FR) *recommended*, Fresco (FC), Pathway (PH), Quarry (QU)
Standard Colors: 3 colors
Warranty: 20 years Commercial, Lifetime Residential
Recycling: Suitable
Test Performance:

| | | |
|-----------------|-----------------------|---------------------------------------|
| ASTM E 648 | Critical Radiant Flux | Class I CRF>0.45 |
| ASTM E 662 | Smoke Density | <450; Good |
| ASTM F 925 | Chemical Resistance | Excellent |
| Slip Resistance | ASTM C 1028* | Very Good (*textures) |
| | ASTM D 2047 | Passes |
| | ADA Compliant | FTC Slip Resistant Classified Product |

MODERN LIME

CS 0602-C Lagos CS 0604-C Porto CS 0606-C Mocha CS 0608-C Branco CS 0610-C Valleta
CS 0612-C Camino CS 0614-C Calypso CS 0616-C Costa CS 0618-C Volga CS 0620-C Niko

Classification: ASTM F 1700 Class III Solid Vinyl Tile
Construction: Multiple layers with backing which contains pre- and post-consumer material
Overall Thickness: .120" / 3 mm (nominal)
Wearlayer Thickness: .032" clear, rigid high density PVC
Size: 12" x 12", 18" x 18", 36" x 36", plus additional custom sizes
Edge: Square, Slight Bevel
Surface Texture: Quarry (QU) *recommended*, Fresco (FC), Frost (FR), Pathway (PH)
Standard Colors: 10 colors
Warranty: 20 years Commercial, Lifetime Residential
Recycling: Suitable
Test Performance:

| | | |
|-----------------|-----------------------|---------------------------------------|
| ASTM E 648 | Critical Radiant Flux | Class I CRF>0.45 |
| ASTM E 662 | Smoke Density | <450; Good |
| ASTM F 925 | Chemical Resistance | Excellent |
| Slip Resistance | ASTM C 1028* | Very Good (*textures) |
| | ASTM D 2047 | Passes |
| | ADA Compliant | FTC Slip Resistant Classified Product |

Style Specifications – Contour Series



PORTOKALI

CS 0561-C Portokali

| | | | |
|-----------------------------|---|-----------------------|---------------------------------------|
| Classification: | ASTM F 1700 Class III Solid Vinyl Tile | | |
| Construction: | Multiple layers with backing which contains pre- and post-consumer material | | |
| Overall Thickness: | .120" / 3 mm (nominal) | | |
| Wearlayer Thickness: | .032" clear, rigid high density PVC | | |
| Size: | 12" x 12", 18" x 18", plus additional sizes | | |
| Edge: | Square, Slight Bevel | | |
| Surface Texture: | Fresco (FC) <i>recommended</i> , Quarry (QU), Frost (FR), Pathway (PH) | | |
| Standard Colors: | 1 color | | |
| Warranty: | 20 years Commercial, Lifetime Residential | | |
| Recycling: | Suitable | | |
| Test Performance: | ASTM E 648 | Critical Radiant Flux | Class I CRF>0.45 |
| | ASTM E 662 | Smoke Density | <450; Good |
| | ASTM F 925 | Chemical Resistance | Excellent |
| | Slip Resistance | ASTM C 1028* | Very Good(*textures) |
| | | ASTM D 2047 | Passes |
| | | ADA Compliant | FTC Slip Resistant Classified Product |

SANTORINI

CS 0551-C Santorini Kafe CS 0553-C Santorini Tandem CS 0557-C Santorini Argos

| | | | |
|-----------------------------|---|-----------------------|---------------------------------------|
| Classification: | ASTM F 1700 Class III Solid Vinyl Tile | | |
| Construction: | Multiple layers with backing which contains pre- and post-consumer material | | |
| Overall Thickness: | .120" / 3 mm (nominal) | | |
| Wearlayer Thickness: | .032" clear, rigid high density PVC | | |
| Size: | 12" x 12", 18" x 18", plus additional custom sizes | | |
| Edge: | Square, Slight Bevel | | |
| Surface Texture: | Pathway (PH) <i>recommended</i> , Fresco (FC), Frost (FR), Quarry (QU) | | |
| Standard Colors: | 3 colors | | |
| Warranty: | 20 years Commercial, Lifetime Residential | | |
| Recycling: | Suitable | | |
| Test Performance: | ASTM E 648 | Critical Radiant Flux | Class I CRF>0.45 |
| | ASTM E 662 | Smoke Density | <450; Good |
| | ASTM F 925 | Chemical Resistance | Excellent |
| | Slip Resistance | ASTM C 1028* | Very Good(*textures) |
| | | ASTM D 2047 | Passes |
| | | ADA Compliant | FTC Slip Resistant Classified Product |

CONTOUR SERIES – WOOD

BLOCKWOOD CP 1201-C Caramel Blockwood CP 1202-C Auburn Blockwood

| | | | |
|-----------------------------|---|-----------------------|---------------------------------------|
| Classification: | ASTM F 1700 Class III Solid Vinyl Tile | | |
| Construction: | Multiple layers with backing which contains pre- and post-consumer material | | |
| Overall Thickness: | .120" / 3 mm (nominal) | | |
| Wearlayer Thickness: | .032" clear, rigid high density PVC | | |
| Size: | 36" x 36" (only) | | |
| Edge: | Square, Slight Bevel | | |
| Surface Texture: | Quarry (QU) <i>recommended</i> , Frost (FR) | | |
| Standard Colors: | 2 colors | | |
| Warranty: | 20 years Commercial, Lifetime Residential | | |
| Recycling: | Suitable | | |
| Test Performance: | ASTM E 648 | Critical Radiant Flux | Class I CRF>0.45 |
| | ASTM E 662 | Smoke Density | <450; Good |
| | ASTM F 925 | Chemical Resistance | Excellent |
| | Slip Resistance | ASTM C 1028* | Very Good (*textures) |
| | | ASTM D 2047 | Passes |
| | | ADA Compliant | FTC Slip Resistant Classified Product |

CONTOUR PLANK

| | | |
|------------------------------|--------------------------|------------------------------|
| CP 3104-C Atlantic Cherry | CP 3105-C Aged Cherry | CP 3106-C Bergerac Beech |
| CP 3201-C Grappa Noce | CP 3205-C Kingwood | CP 3207-C Bolivian Rosewood |
| CP 3210-C Brazilian Cherry | CP 3213-C Trio Walnut | CP 3214-C Camphor Wood |
| CP 3206-C Merrill Birch | CP 3306-C Canadian Maple | CP 3310-C Queensland Walnut |
| CP 3311-C Hawaiian Teak | CP 3312-C Golden Teak | CP 3324-C Washed Teak |
| CP 3313-C Golden Rosewood | CP 0305-C Vintage Tower | CP 0303-C Vintage Chalet |
| CP 0301-C Vintage Lodge | CP 0302-C Vintage Cabin | CP 0306-C Vintage Inn |
| CP 0311-C Summer Savannah | CP 0321-C High Forest | CP 0333-C English Flat |
| CP 3302-C Fruitwood | CP 3301-C Zebrano | CP 3314-C Brown Strata |
| CP 3316-C Olive Strata | CP 3322-C Pale Strata | CP 0355-C Pacific Lighthouse |
| CP 0357-C Driftwood | CP 0359-C Rustic Cedar | CP 0351-C Pacific Boathouse |
| CP 0353-C Pacific Shorehouse | CP 3510-C Metallic Green | CP 3511-C Metallic Gray |
| CP 3512-C Metallic Black | CP 0361-C Newborn | CP 0383-C Wild Bohemian |
| CP 0381-C Wild BosaNova | CP 3320-C Strand Bamboo | |

| | | | |
|-----------------------------|--|-----------------------|---------------------------------------|
| Classification: | ASTM F 1700 Class III Solid Vinyl Tile | | |
| Construction: | Multiple layers with backing which contains pre- and post-consumer material | | |
| Overall Thickness: | .120" / 3 mm (nominal) | | |
| Wearlayer Thickness: | .032" clear, rigid high density PVC | | |
| Size: | 4" x 36", 6" x 36", or 7.2" x 48" | | |
| Edge: | Square, Slight Bevel | | |
| Surface Texture: | Frost (FR), Natural Grain (NG), Rough (RG), Sawn (SW), Tick (TK) Recommended surface for each product is shown on sample in sample book | | |
| Standard Colors: | 44 | | |
| Warranty: | 20 years Commercial, Lifetime Residential | | |
| Recycling: | Suitable | | |
| Test Performance: | ASTM E 648 | Critical Radiant Flux | Class I CRF>0.45 |
| | ASTM E 662 | Smoke Density | <450; Good |
| | ASTM F 925 | Chemical Resistance | Excellent |
| | Slip Resistance | ASTM C 1028* | Very Good (*textures) |
| | | ASTM D 2047 | Passes |
| | | ADA Compliant | FTC Slip Resistant Classified Product |