



Style Specifications – Event Series

All floors shown or listed in this specification shall be Centiva Event Series by International Floors of America, Inc., Florence, AL, 35630.

Specific product shall be: in size " x "
Style Color Series Surface Edge

The Centiva Event Series shall be heterogeneous, resilient flooring with a .030" high density wearlayer. All products shall have an overall gauge of .120" (3 mm) nominal. See individual product specification for sizes offered in each style. The resilient tile shall be manufactured in accordance with ASTM Specification F-1700 and shall be asbestos free. All products shall have a Commercial Limited 20-year Wear Warranty and Residential Lifetime Wear Warranty. The adhesive shall be CENTI 2001 WET SET, CENTI 2000 EP, or CENTI 6000 SP. Installation shall be in accordance with the latest Centiva Installation Guidelines found at www.centiva.com.

The Event Series square tiles may be installed with one-quarter turn (tessellated) or in one direction. For best design appeal and results Centiva recommends the one-quarter turn installation method. Rectangular shaped tiles should be installed in one direction.

GRANITE NS 7131-E Jura Stone NS 7132-E Jomon Stone NS 7133-E Coquina Stone

| | | | |
|-----------------------------|---|-----------------------|---------------------------------------|
| Classification: | ASTM F 1700 Class III Solid Vinyl Tile | | |
| Construction: | Multiple layers with backing which contains pre- and post-consumer material | | |
| Overall Thickness: | .120" / 3 mm (nominal) | | |
| Wearlayer Thickness: | .030" clear, rigid high density PVC | | |
| Size: | 12" x 18", 18" x 18" | | |
| Edge: | Square | | |
| Surface Texture: | Quarry (QU) | | |
| Standard Colors: | 3 colors | | |
| Warranty: | 20 years Commercial, Lifetime Residential | | |
| Recycling: | Suitable | | |
| Test Performance: | ASTM E 648 | Critical Radiant Flux | Class I CRF>0.45 |
| | ASTM E 662 | Smoke Density | <450; Good |
| | ASTM F 925 | Chemical Resistance | Excellent |
| | Slip Resistance | ASTM C 1028* | Very Good (*textures) |
| | | ASTM D 2047 | Passes |
| | | ADA Compliant | FTC Slip Resistant Classified Product |

LIMESTONE NS 7106-E Sea Grass Limestone NS 7107-E Ash Limestone NS 7108-E Minos Limestone

| | | | |
|-----------------------------|---|-----------------------|---------------------------------------|
| Classification: | ASTM F 1700 Class III Solid Vinyl Tile | | |
| Construction: | Multiple layers with backing which contains pre- and post-consumer material | | |
| Overall Thickness: | .120" / 3 mm (nominal) | | |
| Wearlayer Thickness: | .030" clear, rigid high density PVC | | |
| Size: | 12" x 18", 18" x 18" | | |
| Edge: | Square | | |
| Surface Texture: | Quarry (QU) | | |
| Standard Colors: | 3 colors | | |
| Warranty: | 20 years Commercial, Lifetime Residential | | |
| Recycling: | Suitable | | |
| Test Performance: | ASTM E 648 | Critical Radiant Flux | Class I CRF>0.45 |
| | ASTM E 662 | Smoke Density | <450; Good |
| | ASTM F 925 | Chemical Resistance | Excellent |
| | Slip Resistance | ASTM C 1028* | Very Good (*textures) |
| | | ASTM D 2047 | Passes |
| | | ADA Compliant | FTC Slip Resistant Classified Product |

MARBLE

NS 7101-E Serenade Marble NS 7102-E Passion Beige Marble NS 7103-E Mario White Marble

| | | | |
|-----------------------------|---|-----------------------|---------------------------------------|
| Classification: | ASTM F 1700 Class III Solid Vinyl Tile | | |
| Construction: | Multiple layers with backing which contains pre- and post-consumer material | | |
| Overall Thickness: | .120" / 3 mm (nominal) | | |
| Wearlayer Thickness: | .030" clear, rigid high density PVC | | |
| Size: | 12" x 18", 18" x 18" | | |
| Edge: | Square | | |
| Surface Texture: | Frost (FR) | | |
| Standard Colors: | 3 colors | | |
| Warranty: | 20 years Commercial, Lifetime Residential | | |
| Recycling: | Suitable | | |
| Test Performance: | ASTM E 648 | Critical Radiant Flux | Class I CRF>0.45 |
| | ASTM E 662 | Smoke Density | <450; Good |
| | ASTM F 925 | Chemical Resistance | Excellent |
| | Slip Resistance | ASTM C 1028* | Very Good (*textures) |
| | | ASTM D 2047 | Passes |
| | | ADA Compliant | FTC Slip Resistant Classified Product |

RIVER ROCK

NS RR61-E Cortez Gold NS RR64-E Sacred Rock NS RR65-E Tucson Gray,
NS RR72-E Canyon Gray NS RR73-E Mesa Verde NS RR74-E Pueblo,
NS RR75-E New Coronado

| | | | |
|-----------------------------|---|-----------------------|---------------------------------------|
| Classification: | ASTM F 1700 Class III Solid Vinyl Tile | | |
| Construction: | Multiple layers with backing which contains pre- and post-consumer material | | |
| Overall Thickness: | .120" / 3 mm (nominal) | | |
| Wearlayer Thickness: | .030" clear, rigid high density PVC | | |
| Size: | 12" x 18", 18" x 18" | | |
| Edge: | Square | | |
| Surface Texture: | Rock (RK) | | |
| Standard Colors: | 7 colors | | |
| Warranty: | 20 years Commercial, Lifetime Residential | | |
| Recycling: | Suitable | | |
| Test Performance: | ASTM E 648 | Critical Radiant Flux | Class I CRF>0.45 |
| | ASTM E 662 | Smoke Density | <450; Good |
| | ASTM F 925 | Chemical Resistance | Excellent |
| | Slip Resistance | ASTM C 1028* | Very Good (*textures) |
| | | ASTM D 2047 | Passes |
| | | ADA Compliant | FTC Slip Resistant Classified Product |

SANDSTONE

NS 7110-E Pale Sandstone NS 7112-E Cordovan Sandstone

| | | | |
|-----------------------------|---|-----------------------|---------------------------------------|
| Classification: | ASTM F 1700 Class III Solid Vinyl Tile | | |
| Construction: | Multiple layers with backing which contains pre- and post-consumer material | | |
| Overall Thickness: | .120" / 3 mm (nominal) | | |
| Wearlayer Thickness: | .030" clear, rigid high density PVC | | |
| Size: | 12" x 18", 18" x 18" | | |
| Edge: | Square | | |
| Surface Texture: | Frost (FR) | | |
| Standard Colors: | 2 colors | | |
| Warranty: | 20 years Commercial, Lifetime Residential | | |
| Recycling: | Suitable | | |
| Test Performance: | ASTM E 648 | Critical Radiant Flux | Class I CRF>0.45 |
| | ASTM E 662 | Smoke Density | <450; Good |
| | ASTM F 925 | Chemical Resistance | Excellent |
| | Slip Resistance | ASTM C 1028* | Very Good (*textures) |
| | | ASTM D 2047 | Passes |
| | | ADA Compliant | FTC Slip Resistant Classified Product |

Style Specifications – Event Series



OKARA STONE NS 7126-E Okara Gray NS 7127-E Okara Tan

| | | | |
|-----------------------------|---|-----------------------|---------------------------------------|
| Classification: | ASTM F 1700 Class III Solid Vinyl Tile | | |
| Construction: | Multiple layers with backing which contains pre- and post-consumer material | | |
| Overall Thickness: | .120" / 3 mm (nominal) | | |
| Wearlayer Thickness: | .030" clear, rigid high density PVC | | |
| Size: | 12" x 18", 18" x 18" | | |
| Edge: | Square | | |
| Surface Texture: | Quarry (QU) | | |
| Standard Colors: | 2 colors | | |
| Warranty: | 20 years Commercial, Lifetime Residential | | |
| Recycling: | Suitable | | |
| Test Performance: | ASTM E 648 | Critical Radiant Flux | Class I CRF>0.45 |
| | ASTM E 662 | Smoke Density | <450; Good |
| | ASTM F 925 | Chemical Resistance | Excellent |
| | Slip Resistance | ASTM C 1028* | Very Good (*textures) |
| | | ASTM D 2047 | Passes |
| | | ADA Compliant | FTC Slip Resistant Classified Product |

QUARTZITE NS 7230-E Swiss Quartzite NS 7231-E Mediterranean Quartzite, NS 7232-E Moroccan Quartzite NS 7233-E Rosa Quartzite

| | | | |
|-----------------------------|---|-----------------------|---------------------------------------|
| Classification: | ASTM F 1700 Class III Solid Vinyl Tile | | |
| Construction: | Multiple layers with backing which contains pre- and post-consumer material | | |
| Overall Thickness: | .120" / 3 mm (nominal) | | |
| Wearlayer Thickness: | .030" clear, rigid high density PVC | | |
| Size: | 12" x 18", 18" x 18" | | |
| Edge: | Square | | |
| Surface Texture: | Quarry (QU) | | |
| Standard Colors: | 4 colors | | |
| Warranty: | 20 years Commercial, Lifetime Residential | | |
| Recycling: | Suitable | | |
| Test Performance: | ASTM E 648 | Critical Radiant Flux | Class I CRF>0.45 |
| | ASTM E 662 | Smoke Density | <450; Good |
| | ASTM F 925 | Chemical Resistance | Excellent |
| | Slip Resistance | ASTM C 1028* | Very Good (*textures) |
| | | ASTM D 2047 | Passes |
| | | ADA Compliant | FTC Slip Resistant Classified Product |

TRAVERTINE

NS 7210-E Roman Travertine, NS 7211-E Navona Travertine,
NS 7212-E Toscano Travertine, NS 7213-E Silver Travertine

| | | | |
|-----------------------------|---|-----------------------|---------------------------------------|
| Classification: | ASTM F 1700 Class III Solid Vinyl Tile | | |
| Construction: | Layered tile consisting of wearlayer, film, and backing | | |
| Overall Thickness: | .120" / 3 mm (nominal) | | |
| Wearlayer Thickness: | .030" clear, rigid high density PVC | | |
| Size: | 12" x 18", 18" x 18" | | |
| Edge: | Square | | |
| Surface Texture: | Quarry (QU) | | |
| Standard Colors: | 4 colors | | |
| Warranty: | 20 years Commercial, Lifetime Residential | | |
| Recycling: | Suitable | | |
| Test Performance: | ASTM E 648 | Critical Radiant Flux | Class I CRF>0.45 |
| | ASTM E 662 | Smoke Density | <450; Good |
| | ASTM F 925 | Chemical Resistance | Excellent |
| | Slip Resistance | ASTM C 1028* | Very Good (*textures) |
| | | ASTM D 2047 | Passes |
| | | ADA Compliant | FTC Slip Resistant Classified Product |

EVENT PLANK

| | | |
|---------------------------|----------------------------|--------------------------|
| WP OL03-E Cinnamon Olivet | WP OL05-E Allspice Olivet | WP OL07-E Nutmeg Olivet |
| WP 3208-E Wheat Ash | WP 3209-E Burnt Ash | WP 3241-E Natural Cherry |
| WP GW19-E Antique Ochre | WP GW29-E Antique Cimarron | WP GW38-E Antique Walnut |
| WP BB32-E Bamboo | WP 3305-E American Cherry | WP 3308-E Ash |
| WP 3309-E Limed Oak | WP 3307-E European Cherry | WP 3319-E Rock Maple |
| WP 3315-E Mahogany | WP 3317-E Golden Pine | WP 3318-E Knotty Pine |
| WP 3321-E American Oak | WP 3350-E Smoked Oak | WP 3352-E Harvest Oak |
| WP 3354-E Honey Oak | | |

| | | | |
|-----------------------------|---|-----------------------|---------------------------------------|
| Classification: | ASTM F 1700 Class III Solid Vinyl Tile | | |
| Construction: | Layered plank consisting of wearlayer, film, and backing | | |
| Overall Thickness: | .120" / 3 mm (nominal) | | |
| Wearlayer Thickness: | .030" clear, rigid high density PVC | | |
| Size: | 4" x 36" or 6" x 36" | | |
| Edge: | Square | | |
| Surface Textures: | Frost (FR) <i>Bamboo</i> Natural Grain (NG) <i>Rock Maple, Ash, Limed Oak, American Cherry, European Cherry, Natural Cherry, Antique Walnut</i> Rustic (RU) <i>Smoked Oak, Honey Oak, Harvest Oak</i> Third Grain (TG) <i>American Oak, Mahogany, Antique Ochre, Antique Cimarron, Allspice Olivet, Cinnamon Olivet, Nutmeg Olivet</i> Weathered (WE) <i>Knotty Pine, Golden Pine, Wheat Ash, Burnt Ash</i> | | |
| Standard Colors: | 22 colors | | |
| Warranty: | 20 years Commercial, Lifetime Residential | | |
| Recycling: | Suitable | | |
| Test Performance: | ASTM E 648 | Critical Radiant Flux | Class I CRF>0.45 |
| | ASTM E 662 | Smoke Density | <450; Good |
| | ASTM F 925 | Chemical Resistance | Excellent |
| | Slip Resistance | ASTM C 1028* | Very Good (*textures) |
| | | ASTM D 2047 | Passes |
| | | ADA Compliant | FTC Slip Resistant Classified Product |