



# Style Specifications – Victory Series

All floors shown or listed in this specification shall be Centiva Victory Series by International Floors of America, Inc., Florence, AL, 35630.

Specific product shall be: \_\_\_ \_\_\_ \_\_\_ V \_\_\_ \_\_\_ in size \_\_\_" x \_\_\_"  
Style Color Series Surface Edge

The Centiva Victory Series shall be homogeneous or constructed with a .032" high density wearlayer depending on product . All products shall have an overall gauge of .120" (3 mm) nominal. See individual product specification for sizes offered in each style. The resilient tile shall be manufactured in accordance with ASTM Specification F-1700, and shall be asbestos free. All products shall have a Commercial Limited 20-year Wear Warranty and Residential Lifetime Wear Warranty. The adhesive shall be CENTI 2001 WET SET, CENTI 2000 EP, or CENTI 6000 SP. Installation shall be in accordance with the latest Centiva Installation Guidelines found at [www.centiva.com](http://www.centiva.com).

## CANYON COLORS

<b>Classification:</b>	ASTM F 1700 Class III Solid Vinyl Tile		
<b>Construction:</b>	Multiple layers with backing which contains pre- and post-consumer materials		
<b>Overall Thickness:</b>	.120" / 3 mm (nominal)		
<b>Wearlayer Thickness:</b>	.032" clear, rigid high density PVC		
<b>Size:</b>	12" x 12", 12" x 18", 18" x 18", 12" x 36", plus additional custom sizes		
<b>Edge:</b>	Square, Slight Bevel		
<b>Surface Texture:</b>	Fresco (FC) <i>recommended</i> , Frost (FR), Pathway (PH), Quarry (QU)		
<b>Standard Colors:</b>	4 colors		
<b>Warranty:</b>	20 years Commercial, Lifetime Residential		
<b>Recycling:</b>	Suitable		
<b>Test Performance:</b>	ASTM E 648	Critical Radiant Flux	Class I CRF>0.45
	ASTM E 662	Smoke Density	<450; Good
	ASTM F 925	Chemical Resistance	Excellent
	Slip Resistance	ASTM C 1028*	Very Good (*textures)
		ASTM D 2047	Passes
		ADA Compliant	FTC Slip Resistant Classified Product

## CORAL REEF

<b>Classification:</b>	ASTM F 1700 Class III Solid Vinyl Tile		
<b>Construction:</b>	Homogeneous		
<b>Overall Thickness:</b>	.120" / 3 mm (nominal)		
<b>Wearlayer Thickness:</b>	N/A, solid vinyl tile		
<b>Size:</b>	12" x 12", 12" x 18", 18" x 18", 12" x 36", 18" x 36", 36" x 36" plus additional custom sizes		
<b>Edge:</b>	Square, Slight Bevel, Deep Bevel		
<b>Surface Texture:</b>	Slate (SS) <i>recommended</i> , Granite (JS)		
<b>Standard Colors:</b>	23 colors		
<b>Warranty:</b>	20 years Commercial, Lifetime Residential		
<b>Recycling:</b>	Suitable		
<b>Test Performance:</b>	ASTM E 648	Critical Radiant Flux	Class I CRF>0.45
	ASTM E 662	Smoke Density	<450; Good
	ASTM F 925	Chemical Resistance	Excellent
	Slip Resistance	ASTM C 1028*	Very Good (*textures)
		ASTM D 2047	Passes
		ADA Compliant	FTC Slip Resistant Classified Product

## C-TECH

<b>Classification:</b>	ASTM F 1700 Class III Solid Vinyl Tile		
<b>Construction:</b>	Multiple layers with backing which contains pre- and post-consumer materials		
<b>Overall Thickness:</b>	.120" / 3 mm (nominal)		
<b>Wearlayer Thickness:</b>	.032" clear, rigid high density PVC		
<b>Size:</b>	12" x 12", 12" x 18", 18" x 18", 12" x 36", plus additional custom sizes		
<b>Edge:</b>	Square, Slight Bevel		
<b>Surface Texture:</b>	Fresco (FC) <i>recommended</i> , Frost (FR), Pathway (PH), Quarry (QU)		
<b>Standard Colors:</b>	10 colors		
<b>Warranty:</b>	20 years Commercial, Lifetime Residential		
<b>Recycling:</b>	Suitable		
<b>Test Performance:</b>	ASTM E 648	Critical Radiant Flux	Class I CRF>0.45
	ASTM E 662	Smoke Density	<450; Good
	ASTM F 925	Chemical Resistance	Excellent
	Slip Resistance	ASTM C 1028*	Very Good (*textures)
		ASTM D 2047	Passes
		ADA Compliant	FTC Slip Resistant Classified Product

## GLITTER

<b>Classification:</b>	ASTM F 1700 Class III Solid Vinyl Tile		
<b>Construction:</b>	Multiple layers with backing which contains pre- and post-consumer materials		
<b>Overall Thickness:</b>	.120" / 3 mm (nominal)		
<b>Wearlayer Thickness:</b>	.032" clear, rigid high density PVC		
<b>Size:</b>	12" x 12", 12" x 18", 18" x 18", 12" x 36", plus additional custom sizes		
<b>Edge:</b>	Square, Slight Bevel		
<b>Surface Texture:</b>	Frost (FR) <i>recommended</i> , Fresco (FC), Pathway (PH), Quarry (QU)		
<b>Standard Colors:</b>	13 colors		
<b>Warranty:</b>	20 years Commercial, Lifetime Residential		
<b>Recycling:</b>	Suitable		
<b>Test Performance:</b>	ASTM E 648	Critical Radiant Flux	Class I CRF>0.45
	ASTM E 662	Smoke Density	<450; Good
	ASTM F 925	Chemical Resistance	Excellent
	Slip Resistance	ASTM C 1028*	Very Good (*textures)
		ASTM D 2047	Passes
		ADA Compliant	FTC Slip Resistant Classified Product

## MAGICS

<b>Classification:</b>	ASTM F 1700 Class III Solid Vinyl Tile		
<b>Construction:</b>	Homogeneous		
<b>Overall Thickness:</b>	.120" / 3 mm (nominal)		
<b>Wearlayer Thickness:</b>	N/A, solid vinyl tile		
<b>Size:</b>	12" x 12", 12" x 18", 18" x 18", 12" x 36", 18" x 36", 36" x 36" plus additional custom sizes		
<b>Edge:</b>	Square, Slight Bevel, Deep Bevel		
<b>Surface Texture:</b>	Slate (SS) <i>recommended</i> , Granite (JS)		
<b>Standard Colors:</b>	21 colors		
<b>Warranty:</b>	20 years Commercial, Lifetime Residential		
<b>Recycling:</b>	Suitable		
<b>Test Performance:</b>	ASTM E 648	Critical Radiant Flux	Class I CRF>0.45
	ASTM E 662	Smoke Density	<450; Good
	ASTM F 925	Chemical Resistance	Excellent
	Slip Resistance	ASTM C 1028*	Very Good (*textures)
		ASTM D 2047	Passes
		ADA Compliant	FTC Slip Resistant Classified Product

## Style Specifications – Victory Series



### MINERAL CHIP

<b>Classification:</b>	ASTM F 1700 Class III Solid Vinyl Tile		
<b>Construction:</b>	Multiple color chips scattered throughout homogeneous tile		
<b>Overall Thickness:</b>	.120" / 3 mm (nominal)		
<b>Wearlayer Thickness:</b>	N/A, solid vinyl tile		
<b>Size:</b>	12" x 12", 12" x 18", 18" x 18", 12" x 36", 18" x 36", 36" x 36" plus additional custom sizes		
<b>Edge:</b>	Square, Slight Bevel, Deep Bevel		
<b>Surface Texture:</b>	Frost (FR) <i>recommended</i> , Granite (JS), Slate (SS)		
<b>Standard Colors:</b>	7 colors		
<b>Warranty:</b>	20 years Commercial, Lifetime Residential		
<b>Recycling:</b>	Suitable		
<b>Test Performance:</b>	ASTM E 648	Critical Radiant Flux	Class I CRF>0.45
	ASTM E 662	Smoke Density	<450; Good
	ASTM F 925	Chemical Resistance	Excellent
	Slip Resistance	ASTM C 1028*	Very Good (*textures)
		ASTM D 2047	Passes
		ADA Compliant	FTC Slip Resistant Classified Product

### STRIA

<b>Classification:</b>	ASTM F 1700 Class III Solid Vinyl Tile		
<b>Construction:</b>	Multiple layers with backing made from 100% pre- and post-consumer materials		
<b>Overall Thickness:</b>	.120" / 3 mm (nominal)		
<b>Wearlayer Thickness:</b>	.032" clear, rigid high density PVC		
<b>Size:</b>	12" x 12", 12" x 18", 18" x 18", 12" x 36", plus additional custom sizes		
<b>Edge:</b>	Square, Slight Bevel		
<b>Surface Texture:</b>	(SR) Stria		
<b>Standard Colors:</b>	8 colors		
<b>Warranty:</b>	20 years Commercial, Lifetime Residential		
<b>Recycling:</b>	Suitable		
<b>Test Performance:</b>	ASTM E 648	Critical Radiant Flux	Class I CRF>0.45
	ASTM E 662	Smoke Density	<450; Good
	ASTM F 925	Chemical Resistance	Excellent
	Slip Resistance	ASTM C 1028*	Very Good (*textures)
		ASTM D 2047	Passes
		ADA Compliant	FTC Slip Resistant Classified Product

### US SOLIDS

<b>Classification:</b>	ASTM F 1700 Class III Solid Vinyl Tile		
<b>Construction:</b>	Multiple layers with backing which contains pre- and post-consumer materials		
<b>Overall Thickness:</b>	.120" / 3 mm (nominal)		
<b>Wearlayer Thickness:</b>	.032" clear, rigid high density PVC		
<b>Size:</b>	12" x 12", 12" x 18", 18" x 18", 12" x 36", plus additional custom sizes		
<b>Edge:</b>	Square, Slight Bevel		
<b>Surface Texture:</b>	Fresco (FC) <i>recommended</i> , Frost (FR), Pathway (PH), Quarry (QU)		
<b>Standard Colors:</b>	14 colors		
<b>Warranty:</b>	20 years Commercial, Lifetime Residential		
<b>Recycling:</b>	Suitable		
<b>Test Performance:</b>	ASTM E 648	Critical Radiant Flux	Class I CRF>0.45
	ASTM E 662	Smoke Density	<450; Good
	ASTM F 925	Chemical Resistance	Excellent
	Slip Resistance	ASTM C 1028*	Very Good (*textures)
		ASTM D 2047	Passes
		ADA Compliant	FTC Slip Resistant Classified Product